



VHM Industries Private Limited

OPERATIONAL
CONSISTENCY &
EFFICIENCY



TL3070 Telehandler

AT30

TELEHANDLER

Ruggedly constructed for peak performance in tough terrain
and continuous site operations.



INDIA'S NO. 1
CRANE BRAND

SPECIFICATION		4WD
FORWARD REACH		
Forward reach ahead of front tyres 3.5 mtrs		
Max lift height 6.6 mtrs		
LOAD CAPACITIES		
When lifting loads having load centre (LC) 500 mm		
• with boom fully retracted 3 Tons		
• with forward reach of 3 m ahead of tyres 1.5 Tons		
• with forward reach of 2 m, ahead of tyres and lift height of 6 m 1.5 Tons		
ENGINE		
Mahindra (CEV stage IV) Diesel Engine model MCVNC35TI074CE4A 4 cylinder, water cooled, turbo charged with Electronic Control Unit		
• Rated Power 74.5 hp@ 2200 rpm		
• Gradeability with Fork attached and 3 ton load 15°		
TRANSMISSION		
Torque convertor transmission with 4 forward & 4 reverse gear for smooth transmission.		
• Travelling speed, unladen 36 Kmph		
AXLES		
Front Axle	Drive axle rigid mounted	
Rear Axle	Drive axle oscillating type	
Drive modes	4 WD	
STEERING		
Steering modes	2 wheel steer	
BRAKES		
Service brake	Hydraulically actuated wet disc brake	
Parking brake	Hand operated disc brake	
CABIN		
Confirm to ROPS & FOPS. Ergonomically designed cabin to provide excellent all round visibility and maximum comfort to drive		
TYRES		
Front	13.00x24-12PR	
Rear	12.5x80 18-16 PR	
DIMENSIONS		
Ground clearance 350 mm		
Overall height 2.8 mtrs		
Overall width 2.3 mtrs		
Overall length (without fork) 4.98 mtrs		
OPERATIONAL DATA		
Weight without Attachments 7800 Kgs		
Fuel tank capacity 100 Ltrs		
ADDITIONAL FEATURES		
Towing hooks Provided, both in front and rear.		
Fork capacity 3 ton capacity		
Over centre valves for safety Holds the lifted load in position against hose burst		
OPTIONAL VARIENT		
1) 11 mtr 3 Part Boom		
2) Butterfly stabilizers		
3) Crane hook attachment 3T		
4) Bucket 0.25 CuM		
OPTIONAL SAFETY FEATURE		
LMI	For protection against overload a visual indicator is provided to indicate safe and unsafe load working condition. An audio alarm is activated when the load being lifted reaches the maximum safe load.	
Fire Extinguisher, located inside cabin	Qty 01 ABC type, capacity 2 kg	


www.vhmindustries.com

info@vhmindustries.com